

SM 100B25 (100 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
0.18	1.80 - 0.12	*260 - *275 - 310 - 360 - 410 - 460 - 510 - 560 610 - 660 - 710 - 760 - 810 - 860
0.12	1.25 - 0.07	
0.10	1.10 - 0.06	
0.08	0.80 - 0.05	
0.08	0.80 - 0.05	
0.05	0.07 - 0.007	

SM 113B25 (113 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
0.37	4.40 - 0.27	*260 - *275 - 310 - 360 - 410 - 460 - 510 - 560 610 - 660 - 710 - 760 - 810 - 860
0.25	4.40 - 0.17	
0.18	1.60 - 0.11	
0.12	1.10 - 0.07	
0.08	0.31 - 0.05	
0.05	0.06 - 0.008	
0.04	0.10 - 0.033	

SM 127.25 (127 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
0.75	2.60 - 0.16	*250 - *275 - 300 - 325 - 350 - 375 - 400 - 450 - 500 550 - 600 - 650 - 700 - 750 - 800 - 850 - 900 - 950 - 1000
0.55	2.60 - 0.16	
0.37	2.60 - 0.024	
0.25	1.30 - 0.012	
0.18	0.25 - 0.16	
0.13	0.25 - 0.008	
0.10	0.12 - 0.10	

SM 138.25 (138 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
0.75	2.80 - 0.17	*250 - *275 - 300 - 325 - 350 - 375 - 400 - 450 - 500 550 - 600 - 650 - 700 - 750 - 800 - 850 - 900 - 950 - 1000
0.55	2.80 - 0.17	
0.37	2.80 - 0.026	
0.25	1.40 - 0.013	
0.18	0.27 - 0.17	
0.13	0.27 - 0.009	
0.10	0.13 - 0.11	

SM 160.30 (160 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
1.50	4.00 - 0.55	*350 - 400 - 425 - 450 - 500 - 550 - 600 - 650 700 - 750 - 800 - 850 - 900 - 950 - 1000
1.10	2.00 - 0.40	
0.75	2.00 - 0.23	
0.55	2.00 - 0.18	
0.37	1.40 - 0.12	
0.25	1.40 - 0.09	
0.18	1.00 - 0.15	
0.13	1.00 - 0.06	
0.10	0.65 - 0.10	

SM 215.40 (215 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
5.50	4.70 - 0.90	*425 - *450 - 500 - 550 - 600 - 650 700 - 750 - 800 - 850 - 900 - 950 - 1000
4.00	4.70 - 0.90	
3.00	2.90 - 0.65	
2.20	2.90 - 0.45	
1.50	2.90 - 0.28	
1.10	2.90 - 0.26	
0.75	1.40 - 0.19	
0.55	1.40 - 0.12	
0.37	1.10 - 0.12	

SM 315.50 (315 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
7.5	4.10 - 1.10	500 - 550 - 600 - 650 - 700 - 750 800 - 850 - 900 - 950 - 1000 - 1050 - 1100 - 1150
5.5	4.10 - 0.80	
4.0	4.10 - 0.55	
3.0	2.70 - 0.40	
2.2	1.50 - 0.34	
1.5	1.10 - 0.21	
1.1	1.10 - 0.16	

SM 400.60 (400 mm diameter)


(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
15.0	4.60 - 1.30	*600 - *650 - 750 - 800 - 850 900 - 950 - 1000 - 1050 - 1100 - 1150
11.0	4.10 - 1.10	
7.5	4.10 - 0.65	
5.5	3.70 - 0.65	
4.0	3.70 - 0.45	
3.0	1.70 - 0.32	
2.2	1.25 - 0.20	
1.5	0.80 - 0.20	

SM 500A75 (500 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
30.0	3.20 - 1.60	850 - 900 - 950 - 1000 - 1050 1100 - 1150 - 1400 - 1600
22.0	3.20 - 1.60	
18.5	3.20 - 1.60	
15.0	2.10 - 1.00	
11.0	1.60 - 0.80	

SM 620A75 (620 mm diameter)

(kW)	BELTSPEED (m/s)	STANDARD FACE WIDTH (in mm)
30.0	3.90 - 2.00	850 - 900 - 950 - 1000 - 1050 1100 - 1150 - 1400 - 1600
22.0	3.90 - 2.00	
18.5	3.90 - 2.00	
15.0	2.60 - 1.25	
11.0	2.00 - 1.00	



*This face width is not available in all power. Please consult your catalogue.